

SPROCKETS	TYPE	HIGH-STRENGTH STEEL	CORROSION PROTECTED OUTER LINK	CORROSION PROTECTED INNER LINK	STAINLESS STEEL INNER LINK	HOLLOW PINS	COATINGS	DIMENSIONS	PIN LENGTH	ROLLER WIDTH	PIN EJECTION PRESSURE	PIN HARDENING	LINKS/GRAMS	CONNECTOR	RANGE OF USE
11	11SX						Electroless nickel	1/2" x 11/128"	5,6 mm	2,2 mm	>2000 N	XHB	118/270	Connex Link	Roadbike, MTB
	11SB						Black Coating, Brass	1/2" x 11/128"	5,6 mm	2,2 mm	>2000 N	XHB	118/270	Connex Link	Roadbike, MTB
	11S0						–	1/2" x 11/128"	5,6 mm	2,2 mm	>2000 N	XHB	118/270	Connex Link	Roadbike, MTB
	11S E						–	1/2" x 11/128"	5,6 mm	2,2 mm	>2000 N	XHB	124/284, 132/302, 136/311	Connex Link	E-Bike
10	10S1						Electroless nickel	1/2" x 11/128"	5,9mm	2,2 mm	>2000 N	XHB	114/249	Connex Link	Roadbike, MTB
	10SX						Electroless nickel	1/2" x 11/128"	5,9mm	2,2 mm	>2000 N	XHB	114/264	Connex Link	Roadbike, MTB
	10S G						Brass	1/2" x 11/128"	5,9mm	2,2 mm	>2000 N	XHB	114/264	Connex Link	Roadbike, MTB
	10SB						Black Coating, Brass	1/2" x 11/128"	5,9mm	2,2 mm	>2000 N	XHB	114/264	Connex Link	Roadbike, MTB
	10S8						Electroless nickel	1/2" x 11/128"	5,9mm	2,2 mm	>2000 N	XHB	114/264	Connex Link	Roadbike, MTB
	10S0						–	1/2" x 11/128"	5,9mm	2,2 mm	>2000 N	XHB	114/264	Connex Link	Roadbike, MTB
	10S E						–	1/2" x 11/128"	5,9mm	2,2 mm	>2000 N	XHB	124/287, 132/306, 136/315	Connex Link	E-Bike
9	9SX						Electroless nickel	1/2" x 11/128"	6,6 mm	2,2 mm	>2000 N	XHB	114/279	Connex Link	Roadbike, MTB, City/Tour
	9S G						Brass	1/2" x 11/128"	6,6 mm	2,2 mm	>2000 N	XHB	114/279	Connex Link	Roadbike, MTB, City/Tour
	9SB						Black Coating, Brass	1/2" x 11/128"	6,6 mm	2,2 mm	>2000 N	XHB	114/279	Connex Link	Roadbike, MTB, City/Tour
	908						Electroless nickel	1/2" x 11/128"	6,6 mm	2,2 mm	>2000 N	XHB	114/279	Connex Link	Roadbike, MTB, City/Tour
	904						Electroless nickel	1/2" x 11/128"	6,6 mm	2,2 mm	>2000 N	XHB	114/279	Connex Link	Roadbike, MTB, City/Tour
	900						–	1/2" x 11/128"	6,6 mm	2,2 mm	>2000 N	XHB	114/279	Connex Link	Roadbike, MTB, City/Tour
	9S E						–	1/2" x 11/128"	6,6 mm	2,2 mm	>2000 N	XHB	124/303, 132/322, 136/332	Connex Link	E-Bike
8	8SX						Electroless nickel	1/2" x 3/32"	6,8mm	2,4mm	>2000 N	XHB	114/279	Connex Link	Roadbike, MTB, City/Tour
	808						Nickel	1/2" x 3/32"	7,2 mm	2,4mm	>1500 N	XHB	114/319	Connex Link	Roadbike, MTB, City/Tour
	804						Nickel	1/2" x 3/32"	7,2 mm	2,4mm	>1500 N	XHB	114/319	Connex Link	Roadbike, MTB, City/Tour
	800						–	1/2" x 3/32"	7,2 mm	2,4mm	>1500 N	XHB	114/319	Connex Link	Roadbike, MTB, City/Tour
	8S E						–	1/2" x 3/32"	6,6 mm	2,4mm	>2000 N	XHB	124/303, 132/322, 136/332	Connex Link	E-Bike
1	1R8						Nickel	1/2" x 1/8"	10,5mm	3,2mm	>2000 N	case-hardened	112/517	Spring Clip	City/Tour, Heavy Duty
	108						Nickel	1/2" x 1/8"	9,5 mm	3,2mm	>1500 N	case-hardened	112/410	Spring Clip	City/Tour, BMX
	1Z1						Zinc flake	1/2" x 1/8"	9,5 mm	3,2mm	>1500 N	case-hardened	112/410	Spring Clip	City/Tour, BMX
	100						–	1/2" x 1/8"	9,5 mm	3,2mm	>1500 N	case-hardened	112/410	Spring Clip	City/Tour, BMX
	1E8						Nickel	1/2" x 1/8"	10,5 mm	3,2mm	>2000 N	case-hardened	124/573, 132/610, 136/628	Spring Clip	E-Bike

